

# AlphaX S18

## 18" Slim Cinema Subwoofer



### FEATURES

- **Dual ported subwoofer to provide high SPL at very low frequencies**
- **18" Subwoofer delivers with ease, the lowest frequency in your LFE channel**
- **Slim design with front vents enables easy placement of the speaker**

The Alpha Acoustics AlphaX S18 is designed to provide extreme low frequencies especially for the LFE channel. The slim design enables the speaker to be placed behind the screen effortlessly in line with the LCR speakers. The front vented design enables the speaker to be placed close to the back wall.



## ALPHAX S18 SPECIFICATIONS

Design	Front vented sub-woofer
Material	Wood
Frequency response	30 Hz - 1.8 kHz
Transducers	1 x 18" LF
Sensitivity	104 dB
Maximum SPL	130 dB
Impedance	8 $\Omega$
Long term power	800 W
Peak Power	3200 W
Recommended Amplifier Power	1000 W
Input Connectors	Speakon
Dimensions	860 (H) X 530 (W) X 450 (D) mm
Net weight	47 Kg

## APPLICATIONS

### SUBWOOFER FOR CINEMA

*\*Specifications subject to change without notice. 01/2023*

#### Head Office

Alpha Acoustics  
Vinecká 1,  
293 01 Mladá Boleslav  
Czech Republic  
info@alphacoustics.com

#### EMEA Office

Alpha Acoustics DWC-LLC  
BUILDING A3, Office No. DLC-BC-A3-3-OSSD6-04  
Dubai South Business Center,  
Dubai Logistics City  
Dubai, United Arab Emirates