

AMBIENCE C265

50W, 16 Ω , 2-way Co-axial
Ceiling high performance
speaker with dual tweeters



FEATURES

- **Premium quality ceiling speaker for demanding applications**
- **Dual tweeters for crisp audio reproduction**
- **Built in cross over ensures sound clarity**
- **Suitable for high ceiling areas**
- **Excellent frequency response ensuring high quality background music**
- **16 Ohms**
- **Kevlar driver for high fidelity performance**
- **Aesthetic rimless design with ABS enclosure**

The Alpha Acoustics® AMBIENCE C265 is a high performance ceiling speaker with a unique design to cater to the most demanding applications. The speaker has dual tweeters to ensure that the high frequencies travel longer distances as compared to a regular ceiling speaker. In combination with the kevlar cone low frequency driver, the speaker is able to deliver excellent sonic performance. The speaker also is designed with an impedance of 16 Ohms to ensure that more speakers can be connected on one amplifier channel.

AMBIENCE C265T SPECIFICATIONS

Frequency response (-3dB)	60 Hz - 20 kHz
Transducers	LF : 1 X 6.5" HF : 2 X 1" silk dome tweeter
Directivity	120° conical
Sensitivity	89 dB
Maximum SPL	102 dB
Impedance	16 Ω
Power @ 8 Ω	50 W
Enclosure material	ABS with metal grille
Dimensions	235 (Dia) X 160 (H) mm
Hole cut out size	205 (Dia) mm
Net weight	1.9 Kg



APPLICATIONS

Shopping Malls | Homes | Retail stores | Offices | Hotels

Specifications subject to change without notice. 01/2023

Alpha Acoustics

Vinecká 1,

293 01 Mladá Boleslav

Czech Republic

www.alphacoustics.com