

AMBIENCE C45T

15W, compact co-axial ceiling speaker with low impedance and 70/100V operation



FEATURES

- **Co-axial design to ensure coherent distribution of sound**
- **Rimless design ensures pleasing aesthetics**
- **Compact design**
- **Suitable for both PA and BGM applications**
- **Kevlar driver for high fidelity performance**
- **15W ensures great performance to size ratio**
- **Multiple wattage taps available on the 70/100V transformer**
- **Connection terminals that enable quick and easy installation**
- **Aesthetic design with ABS enclosure**

The Alpha Acoustics® AMBIENCE C45T is a small format ceiling speaker suitable for speech and background music which provides excellent performance to size ratio. The speaker has push terminals that enables quick and easy installation. . The co-axial design of the speaker ensures a uniform listening experience. The speaker is suitable for 70/100V operation as well as low impedance application. With the multiple taps available, this speaker will be a perfect fit for commercial audio applications.

AMBIENCE C45T SPECIFICATIONS

Frequency response (-6dB)	80 Hz - 20 kHz
Transducers	LF : 1 X 4.5" HF : 1 X 0.75" co-axial
Directivity	120° conical
Sensitivity	88 dB
Maximum SPL	96 dB
Impedance	8 Ω
Power @ 8 Ω	15W
Power @ 100 V	15 / 7.5 /3.8
Power @ 70V	7.5 /3.8/ 1.5
Enclosure material	ABS with metal grille
Dimensions	170 (Dia) X 170(H) mm
Net weight	1 Kg



APPLICATIONS

Shopping Malls | Retail stores | Offices | Hotels

**Specifications subject to change without notice. 01/2023*

Head Office

Alpha Acoustics
Vinecká 1,
293 01 Mladá Boleslav
Czech Republic
info@alphacoustics.com

EMEA Office

Alpha Acoustics DWC-LLC
BUILDING A3, Office No. DLC-BC-A3-3-OSSD6-04
Dubai South Business Center,
Dubai Logistics City
Dubai, United Arab Emirates