

AMBIENCE W88T

80W, IP66 - Weatherproof Indoor/Outdoor high performance wall speaker



FEATURES

- IP66 design for outdoor applications
- Passive radiator design for extended low frequency output
- Pleasing aesthetics for both indoor and outdoor purposes
- Quick installation using the provided wall brackets
- Combination of both low impedance and 70V/100V options
- Covered euro block connectors facilitate both water proofing and easy installation

The Alpha Acoustics® AMBIENCE W88T is a unique wall mount speaker which can be used for both indoors and outdoors. With a unique bass radiator design, the speaker is able to deliver extended low frequencies which make it suitable for restaurants, outdoor gardens and hospitality projects. The easy to use mounting bracket makes installation easy. The speaker comes with low impedance and 70/100V options making it a true multi-purpose speaker.

AMBIENCE W88T SPECIFICATIONS

Frequency response (-3dB) 38 Hz - 20 kHz

Transducers LF:1 X 8"

HF:1X1"

Directivity 90° (H) X 80° (V)

Sensitivity 87 dB Maximum SPL 115 dB Impedance 8 Ω 80 W Peak Power @ 8 Ω 160 W

Power @ 70V 25 / 12.5 / 6.25 / 3 W Power @ 100V 50 / 25 / 12.5 / 6.25 W Enclosure material ABS with metal grille

Protection IP 66

Color options White / Black

Dimensions 377 (H) X 250 (W) X 238 (D) mm

Net weight 4.9 Kg

APPLICATIONS

Outdoor gardens | Restaurants | Retail stores | Offices | Hotels

Head Office

Alpha Acoustics Vinecká 1, 293 01 Mladá Boleslav Czech Republic info@alphacoustics.com

EMEAI Office

Alpha Acoustics DWC-LLC
BUILDING A3, Office No. DLC-BC-A3-3-OSSD6-04
Dubai South Business Center,
Dubai Logistics City
Dubai, United Arab Emirates

^{*}Specifications subject to change without notice. 01/2023